

STORAGE RACK	L x D x H	Bike Spacing On-Center	Wall Offset to Center of First Bike	Ground Offset to Bottom of Rack	Loading Aisle	Front Offset	Ceiling Min. Height
WALL MAX	3.5 x 8.5 x 18.5"	16"	16"	54 & 63"	42" for bikes + 36"		90"
WALL MAX W/LOCK BAR	6 x 26 x 28.5"	16"	16"	54 & 63"	42" for bikes + 36"		90"
WALL MAX WITH GUARD	4.75 x 8.5 x 62.5"	16"	16"	10 & 19"	42" for bikes + 36"		90"
WM W/GUARD + LOCK BAR	6 x 26 x 62.5"	16"	16"	10 & 19"	42" for bikes + 36"		90"
4 BIKE FREE MAX	71.5 x 36 x 81.5"	18"	18"		47" for bikes + 36"		90"
8 BIKE FREE MAX	71.5 x 60 x 81.5"	18"	18"		47" for bikes + 36"		90"
LOCKING 4 BIKE FREE MAX	71.5 x 36 x 81.5"	18"	18"		47" for bikes + 36"		90"
LOCKING 8 BIKE FREE MAX	71.5 x 60 x 81.5"	18"	18"		47" for bikes + 36"		90"
DOUBLE BIKE STABLE	20 x 32 x 38.25"	16.5"	16"		60" for bikes + 36"	14"	72"
CONDO WALL DOUBLE DECKER							
8 BIKE (4 PER TIER)	63 x 66 x 71"	16"	16"		48"		96"
10 BIKE (5 PER TIER)	79 x 66 x 71"	16"	16"		48"		96"
12 BIKE (6 PER TIER)	95 x 66 x 71"	16"	16"		48"		96"
COWDD W/LOCKING ARMS							
8 BIKE (4 PER TIER)	63 x 66 x 82"	16"	16"		48"		96"
10 BIKE (5 PER TIER)	79 x 66 x 82"	16"	16"		48"		96"
12 BIKE (6 PER TIER)	95 x 66 x 82"	16"	16"		48"		96"

Space requirements are determined by Rudy Rack standards.
 ADA requirements and ordinances may vary by location.

1-800-434-6442
 www.rudyrack.com

